



## OTS PRODUCT OVERVIEW

Pumps Available...  
Anytime, Anywhere.



*The Pump People®*

## Gorman-Rupp OTS Pumps

# Pumps Available Anytime, Anywhere



A



B



C



D

## Self-Priming Centrifugal Pumps

Gorman-Rupp self-priming centrifugal pumps offer maximum dependability and ease of service. Our engine and electric motor-driven, solids-handling trash pumps boast a front cleanout design on most models, allowing for easy trash and debris removal. Where large solids-handling capabilities are not required, Gorman-Rupp offers self-priming, centrifugal pumps specifically designed for medium-head applications. High pressure engine-driven pumps are ideal for dewatering and firefighting or other applications where solids passage is not essential. Some models are equipped with explosion-proof motors and can be used in hazardous environments and/or for handling flammable liquids.

A

### 10 Series®

Engine Driven, Solids-Handling Trash

Size: 2" (50 mm) to 4" (100 mm)  
Max Capacity: 630 GPM (40 lps)  
Max Head: 135' (41 m)  
Max Solids: 3" (76 mm)

B

### O Series® & 60 Series

Engine Driven, High Pressure

Size: 2" (50 mm) to 4" (100 mm)  
Max Capacity: 725 GPM (46 lps)  
Max Head: 380' (116 m)  
Max Solids: .5" (12 mm)

C

### O Series®

Electric Driven, High Pressure

Size: 2" (50 mm)  
Max Capacity: 130 GPM (8 lps)  
Max Head: 58' (18 m)  
Max Solids: .38" (10 mm)  
Horsepower: .75 HP (.56 kW) to 2 HP (1.5 kW)

D

### 80 Series®

Engine Driven, Medium-Head, Minimal Solids-Handling

Size: 2" (50 mm) to 6" (150 mm)  
Max Capacity: 1860 GPM (117 lps)  
Max Head: 210' (64 m)  
Max Solids: 1.9" (49 mm)

**E****F****G****E**

## 10 Series®

Electric Driven, Solids-Handling Trash

Size: 3" (75 mm) to 4" (100 mm)

Max Capacity: 400 GPM (25 lps)

Max Head: 43' (13 m)

Max Solids: 3" (76 mm)

Horsepower: 1.5 HP (1 kW) to 5 HP (3.7 kW)

**F**

## 80 Series

Electric Driven, Medium-Head,  
Minimal Solids-Handling

Size: 1.25" (30 mm) to 1.5" (38 mm)

Max Capacity: 92 GPM (6 lps)

Max Head: 70' (21 m)

Max Solids: .56" (14 mm)

Horsepower: .3 HP (.22 kW) to 2 HP (1.5 kW)

## Priming-Assisted Pumps

Gorman-Rupp's line of ValuPrime® priming-assisted centrifugal pumps is designed to dewater your job site without taking a chunk out of your bottom line. For applications not requiring higher heads and flows, these pumps offer the same quality components you have grown to expect from Gorman-Rupp.

**G**

## ValuPrime®

General Purpose Dewatering

Size: 4" (100 mm) to 6" (150 mm)

Max Capacity: 1520 GPM (96 lps)

Max Head: 112' (34 m)

Max Solids: 3" (76 mm)



H



I



J

## Positive Displacement Pumps

Gorman-Rupp diaphragm, internal gear and hand oscillating positive displacement pumps are designed to handle a variety of viscous fluids. Some models are equipped with explosion-proof motors and can be used in hazardous environments and/or for handling flammable liquids. All positive displacement pumps are self-priming.

H

### D Series

Diaphragm

Size: 2" (50 mm) to 4" (100 mm)

Max Capacity: 150 GPM (9 lps)

Max Head: 25' (8 m)

Max Solids: 2.25" (57 mm)

Horsepower: .5 HP (.37 kW) to 3 HP (2.2 kW)

I

### G Series

Internal Gear

Size: 1" (25 mm)

Max Capacity: 12 GPM (45 lpm)

Max Pressure: 200 PSI (14 bar)

Max Viscosity: 1500 SSU (320 cSt)

Max Temp: 300° F (149° C)

Horsepower: 1.5 HP (1 kW)

J

### HO Series

Hand Oscillating

Size: .75" (19 mm)

Max Capacity: 6 GPM (23 lpm)

Max Pressure: 50 PSI (3 bar)

Max Temp: 120° F (49° C)

# The Right Pump For The Job



K



L

## Electric Submersible Pumps

Gorman-Rupp electric submersible pumps are designed for dewatering when solids are not a concern. These pumps are ideal for flooded basements, pools, spas, ponds, pits or anywhere else a pump can be lowered into water. Some models are equipped with a power cord and level controls.

K

### SE Series

Minimal Solids-Handling, Dewatering

Size: 1.5" (40 mm) to 4" (100 mm)  
Max Capacity: 452 GPM (29 lps)  
Max Head: 87' (27 m)  
Max Solids: .75" (19 mm)  
Horsepower: .3 HP (.22 kW) to 7.5 HP (5.6 kW)

L

### SH Series

Sewage, Shredder

Size: 2" (50 mm) to 4" (100 mm)  
Max Capacity: 280 GPM (18 lps)  
Max Head: 95' (29 m)  
Max Solids: 1.33" (34 mm)  
Horsepower: 1 HP (.75 kW) to 5 HP (3.7 kW)



# After Sale Support

Gorman-Rupp products stand the test of time due to our quality manufacturing processes, rigorous product testing and extensive after sale support.

## Product Support

Every pump manufactured by Gorman-Rupp is supported with reference information. Pump operation and maintenance manuals (including parts lists), specification data sheets, performance curves and outline drawings in PDF and CAD formats are available on our website or through your distributor for every pump.

## Warranty

The warranties on Gorman-Rupp products are some of the best in the industry. Gorman-Rupp has you covered with warranties up to 60 months.

## Education & Safety

Gorman-Rupp is committed to remaining at the forefront of the industry with technology and safety. Training videos, demos and

in-person training sessions created for our distributors and end-users help to keep everyone up to date on the latest safety tips and pump maintenance.

## Parts

When you need a replacement part, you'll have it fast. Gorman-Rupp is fully committed to keeping your equipment running long after installation and ensuring your pump or lift station continues to meet your requirements year after year. We sell parts through our network of distributors. Find a distributor in your area for assistance.

## Service

Should your pump or lift station require service, our worldwide network of factory-trained distributors are ready to quickly respond. Our distributors have the expertise to support you and your pump or lift station long after installation.

## Manufacturing Facilities

**Gorman-Rupp USA**  
Mansfield, Ohio, USA

**Gorman-Rupp Canada**  
St. Thomas, Ontario, Canada

**Gorman-Rupp Europe**  
Waaardenburg, Netherlands  
Namur, Belgium

**Gorman-Rupp Africa**  
Cape Town, South Africa  
Durban, South Africa  
Johannesburg, South Africa (Headquarters)

## Distribution Center

Grand Prairie, Texas, USA

Engineering and manufacturing superiority has been the hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.

**GRPUMPS.COM**

GORMAN-RUPP PUMPS  
P.O. BOX 1217  
MANSFIELD, OHIO 44901-1217 | USA  
TEL: 419.755.1011 | FAX: 419.755.1251



*The Pump People®*