

B 17130

1.75
[44,4]

METRIC DISCHARGE:
50,0 MM, WITH (4) 18,0
MM DIA. HOLES EQUALLY
SPACED ON A 125,0 MM DIA.
B.C. PER DIN 2527, (PN16).

METRIC SUCTION:
50,0 MM, WITH (4) 18,0 MM
DIA. HOLES EQUALLY SPACED
ON A 125,0 MM DIA. B.C.
PER DIN 2527, (PN16).

21.81
[554,0]

16.75
[425,4]

13.50
[342,9]

.69
[17,5]

5.81
[147,6]

11.62
[295,2]

12.75
[323,8]

13.25
[336,6]

10.68
[271,3]

.25/[6,4] × .12/[3,0]
× 2.00/[50,8] LG.
USEABLE KEYWAY

3.53
[89,7]
APPROX.

6.00
[152,4]

1.12
[28,4]
DIA.

2.00
[50,8]

.56/[14,2] DIA.
4 HOLES

7.19
[182,6]

8.90 APPROX.
[226,1]

24.75 APPROX.
[628,6] OVERALL

* 18.00/[457,2] RECOMMENDED FOR
REMOVAL OF BACK COVER PLATE
7.00/[177,8] REQUIRED FOR
REMOVAL OF BACK COVER PLATE

DIMENSIONS:
INCHES
[MILLIMETERS]

07-024



THE GORMAN-RUPP CO.
MANSFIELD, OHIO ST. THOMAS, ONTARIO

DRAWN BY
REP
DATE
7-28-00

SCALE
1/4
REVISED
7-23-07

MODEL
T2A-B /FM
OUTLINE NUMBER
17130