

DISCHARGE:
8.00 NOMINAL WITH 8 HOLES
.88/[22,4] DIA EQUALLY SPACED
ON A 11.75/[298,4] DIA BC

SUCTION:
8.00 NOMINAL WITH 8 HOLES
.88/[22,4] DIA EQUALLY SPACED
ON A 11.75/[298,4] DIA BC

46.54
[1182,0]

8.00
[203,2]

16.38
[415,9]

32.75
[831,8]

34.50
[876,3]

16.22
[411,9]

33.00
[838,2]

17.50
[444,5]

13593

5.00
[127,0]

.50
[12,7]

41.00
[1041,4]

52.50
[1333,5]

.81/[20,6] DIA
6 HOLES

5.00
[127,0]

* 24.00/[609,6] RECOMMENDED FOR REMOVAL OF BACK COVER PLATE
T8AS-B /F / T8CSC-B /F - 13.00/[330,2] REQUIRED FOR REMOVAL OF BACK COVER PLATE
T8DS-B /F / T8ESC-B /F - 14.50/[368,3] REQUIRED FOR REMOVAL OF BACK COVER PLATE

MOTOR FRAMES 284T & 286T

T8AS-B /F
T8CSC-B /F
T8DS-B /F
T8ESC-B /F

DIMENSIONS:
INCHES
[MILLIMETERS]



THE GORMAN-RUPP CO.
MANSFIELD, OHIO ST. THOMAS, ONTARIO

DRAWN BY
RDT
DATE
08-06-25

SCALE
3/32
REVISED

MODEL
NOTED
OUTLINE NUMBER
20007