

DISCHARGE:
8.00-8 NPT

SUCTION:
8.00 NOMINAL WITH 8 HOLES
.88/[22,4] DIA EQUALLY SPACED
ON A 11.75/[298,4] DIA BC

42.29
[1074,1]

43.01
[1092,4]
APPROX

8.00
[203,2]

16.38
[415,9]

32.75
[831,8]

34.50
[876,3]

16.22
[411,9]

33.00
[838,2]

17.50
[444,5]

13593

.50
[12,7]

.81/[20,6] DIA
6 HOLES

5.00
[127,0]

5.00
[127,0]

41.00
[1041,4]

52.50
[1333,5]

* 24.00/[609,6] RECOMMENDED FOR REMOVAL OF BACK COVER PLATE
T8AS-B / T8CSC-B - 13.00/[330,2] REQUIRED FOR REMOVAL OF BACK COVER PLATE
T8DS-B / T8ESC-B - 14.50/[368,3] REQUIRED FOR REMOVAL OF BACK COVER PLATE

T8AS-B
T8CSC-B
T8DS-B
T8ESC-B

MOTOR FRAMES 284T & 286T

DIMENSIONS:
INCHES
[MILLIMETERS]



THE GORMAN-RUPP CO.
MANSFIELD, OHIO ST. THOMAS, ONTARIO

DRAWN BY
RDT
DATE
08-08-25

SCALE
3/32
REVISED

MODEL
NOTED
OUTLINE NUMBER
20008