

MODEL T2A-B


120 X 200 CM



FIBERGLASS ENCLOSURE

- Overall L x W x H : 2105x1300x1430mm
- Enclosure : Composite Honeycomb Sandwich Panels
- Base : Concrete covered with Polyester
- Removable Hinged Doors (External Safety Lock on two Doors)
- Removable Roof and Corners
- Four Lifting Eye Bolts
- Openings through the Base and Central Gutter for Electric Cables
- Large Groutable Opening in the Base for Pipes and Plumbing Accessories
- Ground Anchoring Provisions in the Base, for M20 Anchor Stems
- Forced Air Ventilation System
- External Gelcoat, Grey Colour RAL 7047
- Total Weight : approx. 1500 kg
- Options :
 - Soundproof Insulation
 - Brick or Stone Facings on the Doors and Corners

CUTAWAY



Specifications and illustrations are subject to change without notice / © Copyright by Gorman-Rupp Europe 2015.

SELF PRIMING PUMP T2A-B

ES



Quantity: 1

Size: 2"x2" DN50 DIN Flanges

Maximum Capacity: 50 m³/h

Maximum Head: 32 m

Maximum Self Priming Lift: -7,3 m

Maximum Solids: 38 mm

Model available in Different Materials: T2A3-B /FM, T2A60-B /FM, T2A61-B /FM, T2A71-B /FM and T2A65-B /FM. Refer to The Gorman-Rupp Specification sheet for details on the available pumps.

JAN 2015 GRE

DRIVING SYSTEM

V-belt Transmission: 1 x IEC Electrical Motor, IP55, 50 Hz, Efficiency Class IE2

Safety Transmission Guard

PUMP EQUIPMENT

- 1 x Air Release Valve Gorman-Rupp GRP 33-07 with Isolation Ball Valve and Transparent Hose
- 1 x Pump Casing High Temperature Shutdown Kit
- 1 x Suction and Discharge Pressure Gauge, mounted on a Non-Vibrating Support
- 1 x Pump Casing Drainage System, with Isolation Ball Valve and Transparent Hose

PIPINGS AND PIPING ACCESSORIES

> All Flanges are DIN PN10




- 1 x Suction Pipe in Stainless Steel 304, DN50 Flanged
- 1 x Common Discharge Pipe in Stainless Steel 304 ended by an Expansion Joint, DN50 Flanged
- 1 x Non-Return Valve, DN50 Flanged
- 1 x Eccentric Plug Valve, DN50 Flanged
- 1 x Access Cover on the Discharge Pipe, DN50 Flanged
- 1 x By-Pass Pipe in Stainless Steel 304 on the Discharge Pipe with Eccentric Plug Valve, DN50 Flanged







OTHER INTERNAL EQUIPMENT


- 1 x Electrical Heating Element 750W / 1x230V with Adjustable Thermostat
- 1 x Extraction Fan (325m³/h)
- 1 x Electrical Plug CEE 2P+T 230V 16A
- 1 x Internal Lighting

ELECTRICAL BOX WITH AUTOMATIC LEVEL CONTROL (AVAILABLE AS AN OPTION)

MODEL T2A-B






GORMAN-RUPP EUROPE
 FOMMERTSHED 50
 5120 AA Breda
 The Netherlands
 TEL: +31 206 12 57 74
 FAX: +31 206 12 50 57

Above Ground Lift Station
 Type 120x200
 1 x Pump Gorman-Rupp T2A-B/FM