

Self Priming Centrifugal Pump



**Models 02K3-X2 1P, 02K11-X2 1P, 02K31-X2 1P
02K3-X2 3P, 02K11-X2 3P and 02K31-X2 3P**

Size 2" x 2"

PUMP SPECIFICATIONS

Size: 2" x 2" (51 mm x 51 mm) NPT – Female.

Casing:

(02K3-X2 and 02K11-X2): Gray Iron 30.

(02K31-X2): Ductile Iron 60-40-18.

Maximum Operating Pressure 46 psi (317 kPa).*

Enclosed Type, Four Vane Impeller: Copper Alloy C83600.
Handles 3/8" (9,5 mm) Diameter Spherical Solids.

Replaceable Vane Plate: Gray Iron 30.

Intermediate:

(02K3-X2 and 02K11-X2): Gray Iron 30.

(02K31-X2): Ductile Iron 60-40-18.

Seal: SEE CHART.

Gaskets:

(02K3-X2 and 02K31-X2): NC710 Cork with Nitrile Binder.

(02K11-X2): Teflon.

O-Ring: Fluorocarbon (DuPont Viton® or Equivalent).

Hardware: Standard Plated Steel.

Optional Equipment:

Wheel Kit ^wSemi-Pneumatic Tires. All Iron Construction.

**Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.*



MOTOR DESCRIPTION

Type: Explosion Proof

Horsepower: 2

Frame Size: 56

Voltage: Models 02K3-X2 1P, 02K11-X2 1P and 02K31-X2 1P

Single Phase 115/230 Volts, 60 Hertz
Approx. F.L. Amps: 19.8/9.9

Models 02K3-X2 3P, 02K11-X2 3P and 02K31-X2 3P

Three Phase 230/460 Volts, 60 Hertz
Approx. F.L. Amps: 5.4/2.7

RPM: 3450

MODEL	SEAL DESCRIPTION
02K3-X2 02K31-X2	Type 21, Mechanical, Self-Lubricated. Carbon Rotating Face. Ni-Resist Stationary Face. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F. (71°C).*
02K11-X2	Type 9, Mechanical, Self-Lubricated. Carbon Rotating Face. Ceramic Stationary Face. Teflon Elastomers. Stainless Steel 316 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F. (71°C).*



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice



Printed in U.S.A.

Specification Data

APPROXIMATE
DIMENSIONS and WEIGHTS

NET WEIGHT: 107 LBS. [49 KG.]
SHIPPING WEIGHTS: 120 LBS. [54 KG.]
EXPORT CRATE: 3.6 CU. FT. [.10 CU. M.]

SECTION 30, PAGE 801



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.