PAGE 406 MAY 1999

Stainless Steel

Self Priming Centrifugal Pump



Basic Pedestal Model 13A59-B Size 3" x 3"

PUMP SPECIFICATIONS

Size: 3" x 3" NPT (76 mm x 76 mm) - Female.

Casing: Stainless Steel Alloy 20. Maximum Operating Pressure 66 psi (4,6 kg/cm²).*

Open Type, Two Vane Impeller: Stainless Steel Alloy 20. Handles 1 1/2" (38,1 mm) Diameter Spherical Solids. **Impeller Shaft:** Stainless Steel Alloy 20.

Replaceable Wear Plate: Stainless Steel Alloy 20. Removable Cover Plate: Stainless Steel Alloy 20; 16 lbs. (7 kg).

Pedestal: Gray Iron No. 30. Seal Plate: Stainless Steel Alloy 20. Seal Sleeve: Stainless Steel Alloy 20.

Flap Valve: Fluorocarbon Elastomers (DuPont Viton® or

Equivalent); Stainless Steel Alloy 20. Radial/Thrust Bearing: Open Single Ball.

Bearing Lubrication: Oil.

Flanges: Stainless Steel Alloy 20.


Gaskets: PTFE, Compressed Synthetic Fibers, and Fluorocarbon (DuPont Viton® or Equivalent).

Internal Wetted Hardware: Stainless Steel Alloy 20.

External Hardware: Stainless Steel No. 316.


Optional Equipment: Consult Factory.





13A59-B SEAL DETAIL

Type 9, Mechanical, Self-Lubricated. Silicon Carbide Rotating and Stationary Faces. PTFE Elastomers. Stainless Steel No. 316 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).7



*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.



THE GORMAN-RUPP COMPANY ● MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice


Printed in U.S.A.


Specification Data

SECTION 55, PAGE 406

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 225 LBS. (102 KGS.) SHIPPING WEIGHT: 243 LBS. (110 KGS.) EXPORT CRATE SIZE: 7.7 CU. FT. (0,2 CU. M.)







THE GORMAN-RUPP COMPANY ● MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED • ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

Printed in U.S.A.