Standard Centrifugal Pump

Model 6403A60–B

Size 4” x 3”

FIVE-YEAR WARRANTY 5 6400 SERIES™

PUMP SPECIFICATIONS

Size: 4” x 3” (101,6 mm x 76,2 mm) Flanged.
Casing: Ductile Iron 65-45-12.
Maximum Operating Pressure 61 psi (421 kPa).*
Impeller: Ductile Iron 65-45-12.
Handles 2 1/2” (63,5 mm) Diameter Spherical Solids.
Impeller Shaft: Alloy Steel 4150.
Replaceable Wear Plate: Carbon Steel 1015.
Shaft Sleeve: Alloy Steel 4130.
Seal Plate: Ductile Iron 65-45-12.
Bearing Housing: Gray Iron 30.
Radial Bearing: Open Single Row Ball.
Thrust Bearing: Open Single Row Ball.
Bearing and Seal Cavity Lubrication: SAE 30 Non-Detergent Oil. **Gaskets:** Vegetable Fiber and Cork.
O-Rings: Buna-N. Fluorocarbon FKM, (Viton® or Equivalent)
Hardware: Standard Plated Steel.
Bearing and Seal Cavity Oil Level Sight Gauges.

Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.





SEAL DETAIL

Cartridge Type, Mechanical, Oil-Lubricated, Double Floating, Self-Aligning. Silicon Carbide Rotating and Stationary Faces. Stainless Steel 316 Stationary Seat. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).*

© Copyright Gorman-Rupp Pumps 2024

Specification Data

SECTION 64, PAGE 300

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT:	**355 LBS. (161 KG.)***
SHIPPING WEIGHT:	**445 LBS. (202 KG.)***
EXPORT CRATE:	**10.0 CU. FT. (0,28 CU. M.)**





© Copyright Gorman-Rupp Pumps 2024