## For Power-Take-Off Drive

Sec. 110

PAGE 810

SEPTEMBER 2011

Q



# **Standard Centrifugal Pump**

# Model 66C3-GE(HYD)

Size 6" x 6"

#### **PUMP SPECIFICATIONS**

Size: 6" x 6" (152 mm x 152 mm) Victaulic<sup>®</sup>.

Casing: Ductile Iron 60-40-18.

Maximum Operating Pressure 208 psi (1434 kPa)\*.

Enclosed Type, Eight Vane Impeller: Copper Alloy C83600.

Handles 7/8" (22 mm) Diameter Spherical Solids.

Pinion Shaft: Alloy Steel 8620.

Two Replaceable Wear Rings: Copper Alloy C83600.

Motor Adaptor: Ductile Iron 80-55-06.
Suction Head: Ductile Iron 60-40-18.
Gear Box Housing: Gray Iron 30.
Gear Lubrication: SAE 90 Gear Oil.

Gears: Alloy Steel 8620. Gear Ratio: 2.19:1 Increase.

Radial and Thrust Bearings: Open Single Row Ball.


Gaskets: Vegetable Fiber and Cork. Hardware: Standard Plated Steel.


Standard Equipment: 6" Victaulic Goose Neck Suction (may be rotated in 30° intervals). Hydraulic Motor Adaptor for SAE "C" and "CC" Motor Flanges.

Optional Equipment: Consult Factory for Additional Options.

\*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.

Victaulic is a Registered Trademark of Victaulic Company of America.





#### **SEAL DETAIL**

Type 21, Mechanical, Self-Lubricated. Carbon Rotating Face. Ni-Resist Stationary Face. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F. (71°C.)\*



#### THE GORMAN-RUPP COMPANY ● MANSFIELD. OHIO

GORMAN-RUPP OF CANADA LIMITED • ST. THOMAS, ONTARIO, CANADA

www.grpumps.com

Specifications Subject to Change Without Notice


Printed in U.S.A.


#### **Specification Data**

SECTION 110, PAGE 810

# APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: SHIPPING WEIGHT: DOMESTIC CARTON: 185 LBS. [83,9 KG.] 209 LBS. [94,8 KG.] 11.9 CU. FT. [0335 CU. M.]







### THE GORMAN-RUPP COMPANY • MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED • ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

Printed in U.S.A.